



Mobile Computing Solution



Rugged, Multi-functional Computing for Severe Environments

The ST395BT features the integration of a 9" capacitive touch screen and a high performance, energy-efficient Intel® dual core processor within a slim, lightweight, durable package.

With built-in Wi-Fi and Bluetooth connection as well as options for smart card reader, RFID reader, barcode scanner, camera, and 3G module, this robust tablet offers seamless information capture and transmission for improved workflow.

Rated IP65, MIL-STD-810G/ MIL-STD-461F and certified with wide temperature range (-10°C to 40°C), the ST395BT provides reliable operation in harsh, mission-critical environments.



Features

- 9" LED-backlight screen with capacitive touch; antireflection outdoor viewable
- Support for Microsoft® Windows® Embedded Standard 7, 7 Professional or Linux operating system
- Intel[®] Celeron[®] dual core processor; high performance with low power consumption
- ► IP65-rated for water and dust resistance
- ▶ Rated MIL-STD-810G for shock and vibration protection
- ► MIL-STD-810G Explosive Atmosphere certified
- ► MII -STD-461F for FMI and FMC tolerance
- NIST (National Institute of Standards and Technology) compliant
- TPM (Trusted Platform Module) 1.2 support
- Wi-Fi and Bluetooth 4.0 connection
- Built-in gyroscope sensor, e-compass sensor, and 3axis accelerometer
- Hot-swappable batteries and vehicle-mount charging option
- Optional Camera, 2D Barcode Scanner, RFID Reader,
 3G Module and Half slot smart card reader

Mobile Computing Solution

Accessories

External Battery Pack

Snap-on, hot swappable battery pack.

Doubles duration of mobile operation.

Li-ion, 28W.



 6-Bay External Battery Charger

Charges up to six External Battery Packs simultaneously.

Power supply is included.



External Battery Charger Kit

Recharges the external battery pack "offline" without affecting usage of the device.

Power Supply is included.



Desktop Charging Cradle

Docking support with ports for Power, 2 x USB and Ethernet.

Power supply is not included.



Wall / Vehicle Mount Cradle

Wall / vehicle mountable lockable mount. Support for Power, 2 x USB and Ethernet. Power supply is not included.



Automobile Power Adapter

Use with power outlets in vehicles to facilitate device usage and/or battery recharge.



 Tablet Carry Case with Compact USB Keyboard

Custom fitted for the protection, handling and usage of the Tablet. Includes compact USB Keyboard (USA layout only)



Padded Shoulder Strap

Padded for comfort, provides convenient mobile operation. Strap is adjustable and can be attached to the Rubber Grips.



Plastic Tablet Handstrap

Designed for secure handling and easy cleaning.



Screen Protectors

Replaceable custom-fitted screen protectors shield your display screen from fingerprints, scratches and dust, while maintaining comfortable input.

10 sheets per package



Mobile Computing Solution

| Specification | |
|----------------------------|---|
| System | ST395BT |
| СРИ | Intel [®] Celeron [®] Dual Core, 1.58GHz (up to 2.17GHz) |
| RAM | 4GB |
| Storage | 32GB to 256GB Flash |
| Operating System | Microsoft® Windows® Embedded Standard 7, Windows® 7 Professional, or Linux |
| Display | 9" LED-backlight screen with capacitive touch; anti-reflection outdoor viewable |
| Display Resolution | 1024 x 600 (WSVGA) |
| Network Interface | Wi-Fi 802.11ac; 2.4GHz/ 5GHz dual band; Bluetooth 4.0 |
| Trusted Platform Module | TPM 1.2 support |
| Control Switch and Buttons | 1 power button, 1 trigger button and 1 Wi-Fi switch |
| Indicator | 1 Power/ Battery status LED and 1 WLAN active LED |
| Microphone | Built-in Microphone |
| Speaker | Built-in speakers |
| Sensor | Built-in gyroscope sensor, e-compass sensor, pressure sensor and 3-axis accelerometer |
| I/O Ports | |
| USB 2.0 port | 1 |
| Headphone-out | 1 |
| DC-in | 1 |
| Smart Card Reader | Half-slot, reads ISO 7816 T=0, T=1; 1.8/3/5V smart card (optional) |
| SD Slot | 1 full size SD card slot |
| Mechanical | |
| AC/DC Adapter | Input: 100 – 240V AC; Output: 19V DC, 2.36A |
| Battery Pack | Internal 7.4V, 3760mAh/ Optional: External 7.4V, 3760mAh |
| Enclosure | ABS + PC plastics |
| Stylus | Yes, non-electronic tip |
| Protective Grips | Rubber bumpers on each corner for handling protection |
| Dimensions (H x W x D) | 196 x 256 x 33.5 mm 7.7 x 10 x 1.3 in |
| Weight | 1.1 kg / 2.43 lbs |

| Specification | |
|-----------------------------------|---|
| System | ST395BT |
| Water and Dust Resistance | IP65 |
| Regulatory | FCC Class B, CE, RoHS, NIST compliant |
| Vibration and Shock Resistance | MIL-STD-810G |
| Explosive Atmosphere | MIL-STD-810G |
| EMI and EMC tolerance | MIL-STD-461F |
| Temperature | Operation: -10°C – 40°C; Storage: -20°C – 60°C |
| Humidity | 0% – 90% non-condensing |
| Barcode Scanner (optional) | 2D barcode scanner; also reads 1D |
| Camera (optional) | 5 megapixel back camera with LED flash |
| WWAN or GPS (optional) | 3G module for HSPA+/EV- DO/WCDMA/EDGE/GPRS/GSM with GPS positioning and navigation (optional) |
| RFID Reader (optional) | Integrated UHF RFID Reader: 917.1 to 923.3 MHz, complies with ISO 18000-6c/ EPC global Gen II |
| | |



For more information, including pricing, availability and detailed features please look at our web site at www.sumotech.com or email sales@sumotech.com

SUMO Technologies Ltd, Manor Chambers, Marygate, YORK YO30 7BH Tel: +44 (0) 1904 670670 Fax: +44 (0) 1904 670570

All specifications are subject to change without notice.

SUMO, Masters of Technology and ST395BT are trademarks of SUMO Technologies Ltd. All other products and services are trademarks or service marks of their respective companies, and are acknowledged. **E&OE**